

PD 14000

PALLET DOLLY



CHASSIS

The chassis is produced by steel profiles. The walkway is covered with bored steel sheet to prevent slipping and provides drainage. The PD7000 is side-towed and end-loaded and PD14000 is end-towed and end-loaded.

STEERING & BRAKING SYS.

The mobility of the unit is provided by fixed rear wheels and 360° swivel type front wheels which ensure high maneuverability capacity. The rear wheels are equipped with a brake system that is applied when tow-bar is upright position.

ROLLERS

The rollers are produced by 2 ½" galvanized pipes with bearings at both ends arranged in an order of two rows to ensure easy operations of the pallet.

GUIDE RAILS

The both sides of the upper chassis provide adequate guide rails made of steel sheet to prevent the load from falling off.

STOPS

The upper chassis provides special retractable stops made of steel sheet to be used to restrain containers firmly.

SURFACES

The chassis is hot-dip galvanized.

OPTIONS

Stops for P2 (PD7000)

Stops for P1-P2-P4-P6 (PD14000)

Custom painting, three rows of rollers, four rows of rollers, turntable for loading platform (PD7000), spare wheel.



www.timsan-gse.com

Eyüp Sultan Mh. Kartopu Sk. No.7

Sancaktepe, İstanbul, Turkey

+90 216 527 4270